

Optimized Thermosiphon Cooling

Optimum Cooling for Circulators and Pushers





OPTIMIZATION OPTIONS FOR COOLING OF CIRCULATORS AND PUSHERS

In the past, central cooling systems were used to cool the components of the plants. They could be operated with various media that were functional, but which also had some inherent disadvantages: With central cooling systems, cooling is provided only if the media feeds are functional; the failure of which could lead to considerable damage to the circulators and pushers.

Water cooling:

- Limescale can lead to clogging of the lines over time and may cause the cooling system to fail
- Water as a medium should be avoided in heat treatment systems for safety reasons – especially when combined with oil and salt baths
- Power failures and faulty media feeds cause the cooling system to fail

Air cooling:

- Noise pollution from the blower
- Prone to line contamination
- Power failures and faulty media feeds cause the cooling system to fail
- Oil cooling:
 - Power failures and faulty media feeds cause the cooling system to fail


THE AICHELIN ADVANCE: THERMOSIPHON COOLING

The original version: cooling circuit together with the circulator or pusher

- Warming up the heat transfer oil, the medium rises through line 1
- Cooling the oil via the cooling element, sinking of the oil into the aggregate through **line 2**
- Result: an autonomous circulation without conveyance by a drive
- Increased serviceability of the respective units together with the shut-off valves on both sides of the flanges

Advanced development thermosiphon cooling:

- Increased lowering of temperature of the heat transfer oil than in the original version thanks to the optimized cooling element
- Increasing the cooling capacity by yielding optimized aggregate cooling
- Improvement of the reliability of the cooled unit until the next maintenance



YOUR ADVANTAGES

- Virtually maintenance-free
- Operational and process safety
- Modular design

- Compatible with previous versions as well as water and air cooling systems - easy conversion
- Longer aggregate lifetime thanks to improved cooling capacity
- Widely proven product from AICHELIN

YOUR RELIABLE PARTNER

- Competent engineering partner
- Reliable supplier of components

- High level of expertise in plant modernization
- Perfect integration into your AICHELIN plant by the original manufacturer

Technical changes reserved. AICHELIN® is a registered trademark. ASG_17OR_E_2001

AICHELIN Service GmbH

Schultheiß-Köhle-Straße 7 D-71636 Ludwigsburg Tel.: +49 7141 64 370 Fax: +49 7141 64 371 00 service.de@aichelin.com

AICHELIN Ges.m.b.H. Fabriksgasse 3

Fabriksgasse 3 A-2340 Mödling Tel.: +43 2236 23 64 60 Fax: +43 2236 22 229 service.at@aichelin.com